

## Environmental Stewardship: Controlling Silage Leachate

*Dann Bolinger, Dairy Agent*

*Natalie Rector, Nutrient Management Agent*

*Becky Mitchell, Former Dairy Agent*



Silage leachate, or seepage from silage piles, bags, bunkers, or silos often occurs on dairy farms. Michigan's guidelines for a Comprehensive Nutrient Management Plan (CNMP), silage leachate is identified among manure and milkhouse wastewater on the list of farm outputs requiring proper management.

Why such concern over silage leachate? From an environmental standpoint, leachate presents a problem when it flows into surface waters. Silage leachate has an extremely high biochemical oxygen demand (BOD). This means that leachate has a very high potential for oxygen consumption and when discharged into surface water, can remove so sufficient oxygen that fish and other aquatic creatures die. As little as 1 gallon of silage leachate can lower the oxygen content of 10,000 gallons of river water to a critical level for fish survival.

Silage leachate also contains nutrients that can harm groundwater; the most critical being nitrate-nitrogen. In addition, the acidic nature of silage leachate can burn or kill vegetation in the area where it drains. Farmers can opt to capture silage leachate by constructing lined ponds or collection basins. Such structures must meet prescribed setbacks from existing wells

and surface water and are generally costly to construct. Systems can also be engineered which decrease the volume of material to be handled by collecting only the concentrated wastes while diverting the low-concentrated wastes to a designed grass filter area.

Once captured, leachate could be pumped or directed into an existing manure or milk house wastewater storage. However, this could contribute a significant amount of volume to the storage, particularly when rainwater runoff from a bunker silo is collected. Moreover, since leachate may produce dangerous hydrogen sulfide when mixed with liquid manure, it should only be added to well-ventilated, outdoor storages.

As an alternative to costly structures to catch silage leachate, farmers can and should make efforts to minimize silage leachate production. Fortunately, many of the recommended practices for harvesting and storing the highest quality silage go hand in hand with minimizing silage leachate. One of the most critical determinants of silage quality and leachate production is moisture of the forage at the time of harvest. Corn silage for bunker silos should be harvested between 65 percent and 70 percent moisture (30 to 35 percent dry matter). Moisture levels can be even lower for corn silage stored in upright silos or bags, though it should not fall below 60 percent moisture. A range of 60 to 70 percent moisture (30 to 40 percent dry matter) is optimal for alfalfa haylage harvest.

Silage harvested at higher than prescribed moisture levels can produce



substantially more leachate. Leachate can have negative production-related consequences. It removes nutrients, particularly soluble nitrogen and carbohydrates, from the forage. Leachate can damage the silo structure because of its corrosive characteristics. In addition, silage harvested at higher than prescribed moistures tends to have a higher prevalence of *Clostridia* bacteria. Such bacteria produce nitrogen compounds and butyric acid which can reduce animal feed intake and silage protein levels.

Covering the silage is another important management practice for minimizing leachate. Not only do covers preserve forage quality by minimizing airflow into the pile, covers also reduce leachate production by preventing rainfall from penetrating the silage and



solublizing nutrients. A plastic covering secured with tires is one common approach to protect forage quality. Research at Kansas State University shows that covering a bunker silo with plastic can return \$8 in reduced forage losses for every \$1 spent. Additionally, from an animal performance standpoint, covering a bunker preserves feed value and improves palatability and feed intake.

Plastic covers should be applied so that rainwater and snowmelt is channeled *off* of the forage pile. The all too common practice of simply diverting water to the walls of the bunker silo

should be avoided since water penetrating silage along the walls will still result in a leachate problem. Maintenance of plastic also needs consideration; any holes in the covering of a silo or bag should be repaired immediately.

Though the flow of silage leachate will be greatest during the first month following filling of a storage unit, leachate will occur in smaller amounts throughout the feed-out period, particularly when rainfall has access to the pile. The loading area should be kept clean of spilled silage. Silage that is not cleaned off of the loading area could wash offsite with rainwater and when wet, will continue to produce silage leachate. Divert rainwater away from silage storage whenever possible. Keeping open bunker silo faces vertical will also minimize contact with rainwater and reduce spoilage. An emergency backup plan should be developed for those years when high moisture silage is unavoidable. Temporary runoff containment measures could be used, such as using sawdust to absorb and stop silage leachate runoff. The sawdust could then be collected and applied to fields.

Although heightened awareness of silage leachate and runoff is necessary at harvest time, it poses a serious environmental risk year round. As responsible stewards of the environment, all producers need to be aware of the risk of silage leachate and take appropriate steps to reduce and manage it. If you would like further assistance in assessing your particular silage leachate management situation, seek assistance from one or more of the following resource persons: MSU Extension Dairy or Livestock Agents, your county USDA Natural Resource Conservationist, or a qualified engineering consultant.